

J-DRain[®] Prefabricated Drainage Composites

JDR Disclaimer, Limitations, & Limited Warranty

Limitations: J-DRain is resistant to chemicals in normal soil environments. However, some reagents may affect the performance of J-DRain. A JDR representative should be contacted for further information to determine the suitability of use of J-DRain in unusual soil environments. J-DRain should be limited to its exposure to ultra-violet sunlight. J-DRain should be backfilled or covered within seven days of installation.

Limited Warranty: JDR Enterprises, Inc. (JDR) warrants its materials to be free from defects in workmanship and materials only at the time of shipment from our manufacturing facility. If any JDR materials prove to contain defects that substantially affect the performance of the product, JDR will, at its option, replace the material or refund its purchase price. This limited warranty is the only warranty extended by JDR with respect to its materials. There are no other warranties, including implied warranties of merchantability and fitness for a particular purpose. JDR specifically disclaims liability for any incidental, consequential, or damages to a structure or its contents, arising under theory of law whatsoever. The dollar value of JDR's liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the JDR material in question.

Disclaimer: All information, drawings and specifications are based on the latest published information at the time of printing. JDR reserves the right to make changes due to manufacturing improvements and engineering at any time. All physical properties are minimum average roll values (MARV). Standard variations of 10% in mechanical properties and 15% in hydraulic properties are normal.