





# J·DRAIN<sup>®</sup> GRS

## Green Roof Drainage System

### APPLICATIONS:

GREENROOFS

PLANTERS



### Advantages:

- ♦ Low cost
- ♦ Polypropylene core
- ♦ Filters fine particles
- ♦ Easy install / No loose fabrics
- ♦ Pre-assembled drain system
- ♦ Root, mildew & rot resistant
- ♦ Water retention chambers (1.1 gal/10 sq. Ft.)
- ♦ Reduces weight of greenroof (no gravel)

### Product Description:

**J-DRAIN GRS** consists of a impermeable polymeric sheet cusped under heat and pressure to form a high flow dimpled drainage core. The core is perforated, then bonded to top root resistant filter fabric and bottom protection fabric, specifically designed for Green roof applications. The top root resistant filter fabric prevents roots from affecting the efficiency of the drainage/aeration layer and retains soil or other fine particles from being washed away and allows water to pass into the drainage core. The bottom protection fabric safeguards the waterproofing membrane. The core is installed dimple side down to allow water retention. The excess water is collected and conveyed to a proper collection system..

### Physical Properties

Core		Fabric	
Compressive Strength (ASTM D-1621)	9,500 psf 455 kNm2	<b>Fabric Type</b>	<b>ECO</b> (top grey)
Thickness (ASTM D-1777)	1.0 in. 2.54 cm.		<b>Protection</b> (bottom black)
Flow (ASTM D-4716)	30 gal/min/ft 372 l/min/m	Apparent Opening Size (ASTM D4751)	50 US Sieve
Hydraulic gradient = .1		Grab Tensile (ASTM D5034)	75 lbs
Water Retention	1.1 gal/10 sq ft.	Grab Elongation (ASTM D5034)	40%
		CBR Puncture (ASTM D6241)	160 lbs.
Roll Weight	88 lbs.	Water Flow Rate (ASTM D4491)	165 gal/min/ft <sup>2</sup>
Roll Width	4 ft.	Permittivity (ASTM D4491)	1.8 sec <sup>-1</sup>
Roll Length	50 ft.		

The information contained herein is believed by JDR Enterprises, Inc. to be accurate and is offered solely for the customer's consideration, investigation and verification. Determination of suitability for use is the responsibility of the user. JDR's Limitations, Limited Warranty, & Disclaimer along with Standard Terms & Conditions apply. See [www.j-drain.com](http://www.j-drain.com) for more info. Limitations: J-DRAIN is resistant to chemicals in normal soil environments. However, some reagents may affect the performance of J-DRAIN. A JDR representative should be contacted for further information to determine the suitability of use of J-DRAIN in unusual soil environments. J-DRAIN should be limited to its exposure to ultra-violet sunlight. J-DRAIN should be backfilled or covered within seven days of installation. Disclaimer: All information, drawings and specifications are based on the latest published information at the time of printing. JDR reserves the right to make changes due to manufacturing improvements and engineering at any time. All physical properties are minimum average roll values (MARV). Standard variations of 10% in mechanical properties and 15% in hydraulic properties are normal.

[info@j-drain.com](mailto:info@j-drain.com)
[www.j-drain.com](http://www.j-drain.com)

**JDR** Enterprises, Inc.

292 S. Main St., Suite 200 Alpharetta, GA 30009  
(800) 843-7569 (770) 442-1461 Fax: (770) 664-7951